



Product APPLICATION Guide

Electromechanical Indicators (with Circuitry)




Flange Mount- Wires

Part Number	Sound Level @ 30 cm	Freq. (Hz)	Operating Voltage (Vdc)	Current (mA)	Size L x W x H (mm)	Flange Hole Spacing (mm c/c)
Continuous Tone						
PK-16N04WA-01Q	75 @ 1.5Vdc	400	1.5 - 2	30 @ 1.5Vdc	24x17x15	27
PK-16N04WA-03Q	82 @ 3Vdc	400	2 - 4	30 @ 3Vdc	24x17x15	27
PK-16N04WA-06Q	85 @ 6Vdc	400	4 - 8	30 @ 6Vdc	24x17x15	27
PK-16N04WA-12Q	85 @ 12Vdc	400	8 - 16	35 @ 12Vdc	24x17x15	27
PK-16N04WA-24Q	85 @ 24Vdc	400	20 - 28	35 @ 24Vdc	24x17x15	27




Flange Mount- Wires

Part Number	Sound Level @ 30 cm	Freq. (Hz)	Operating Voltage (Vdc)	Current (mA)	Size Dia x Hgt (mm)	Flange Hole Spacing (mm c/c)
Continuous Tone						
PK-26N04W-03VQ	80 @ 3Vdc	400	2 - 4	30 @ 3Vdc	26 x 15	32
PK-26N04W-06VQ	85 @ 6Vdc	400	4 - 8	30 @ 6Vdc	26 x 15	32
PK-26N04W-12VQ	87 @ 12Vdc	400	8 - 16	40 @ 12Vdc	26 x 15	32
PK-26N04W-24VQ	90 @ 24Vdc	400	20 - 28	25 @ 24Vdc	26 x 15	32




Flange Mount- Wires

Part Number	Sound Level @ 30 cm	Freq. (Hz)	Operating Voltage (Vdc)	Current (mA)	Size Dia x Hgt (mm)	Flange Hole Spacing (mm c/c)
Repeating Ding Dong Tone (1 Ding Dong Every 2 Sec)						
PB-32N10W-12K	80 @ 12Vdc	1010 - 1230	6 - 18	125 @ 12Vdc	31.7 x 24.6	39



Flange Mount- Flat Blade Terminals

Part Number	Sound Level @ 30 cm	Freq. (Hz)	Operating Voltage (Vdc)	Current (mA)	Size L x W x H (mm)	Flange Hole Spacing (mm c/c)
Continuous Tone						
PK-26N04P-06AQ	85 @ 3Vdc	450	4 - 8	40 @ 6Vdc	26x26x20	32
PK-26N04P-12AQ	80 @ 12Vdc	400	8 - 14	45 @ 12Vdc	26x26x20	32



PC Pins

Part Number	Sound Level @ 30 cm	Freq. (Hz)	Operating Voltage (Vdc)	Current (mA)	Size L x W x H (mm)	PC Pin Pitch (mm c/c)
Continuous Tone						
PK-16N04P-06AQ	80 @ 6Vdc	400	4 - 8	30 @ 6Vdc	23x16.5x14	15

Call 317-612-1000 or Visit www.mallory-sonalert.com for More Details