




MALLORY SONALERT PRODUCTS, INC.

Product APPLICATION Guide

Cage Code - 90201



Screw Neck Panel Mount

Screw Neck Panel Mount- Military/Rugged

Non-RoHS Part No.	Min Sound Level @ 2ft	Freq.	Operating Voltage	Max Current	Size Dia x Len	Termination Type	National Stock Numbers
Loud Sound Level- Continuous Tone							
SC110MN	80 – 95 dBa	2900 Hz	30-120 Vac/dc	6 – 24 mA	1.69 x 1.38”	Screw Terms	6350015196472
SC616MN	80 – 95 dBa	2900 Hz	6-16 Vdc	6 – 22 mA	1.69 x 0.81”	Screw Terms	6350011826056
SC628MN	80 – 90 dBa	2900 Hz	6-28 Vdc	4 – 16 mA	1.69 x 0.81”	Screw Terms	6350012512607
SC648MAN	80 – 95 dBa	2900 Hz	10-48 Vac/dc	4 – 26 mA	1.69 x 1.38”	Screw Terms	6350015655554
Medium Sound Level- Continuous Tone							
SC110M	68 – 80 dBa	2900 Hz	30-120 Vac/dc	4 – 18 mA	1.69 x 1.38”	Screw Terms	6350014890357
SC110MH	68 – 80 dBa	4500 Hz	30-120 Vac/dc	5 – 18 mA	1.69 x 1.38”	Screw Terms	6350014367709
SC250M	68 – 80 dBa	2900 Hz	60-250 Vac/dc	4 – 10 mA	1.69 x 1.38”	Screw Terms	6350010621721
SC628M	68 – 80 dBa	2900 Hz	6-28 Vdc	4 – 14 mA	1.69 x 0.81”	Screw Terms	5895010746781
							6350002670442
							6350011178031
							6350012786949
6350014411396							
SC628MA	68 – 80 dBa	2900 Hz	6-28 Vac/dc	4 – 22 mA	1.69 x 1.38”	Screw Terms	6350011296462
SC628MAH	68 – 80 dBa	4500 Hz	6-28 Vac/dc	4 – 16 mA	1.69 x 1.38”	Screw Terms	
SC628MD	60 – 75 dBa	1900 Hz	6-28 Vdc	5 – 20 mA	1.69 x 0.81”	Screw Terms	6350010837816
SC628MH	68 – 80 dBa	4500 Hz	6-28 Vdc	4 – 14 mA	1.69 x 0.81”	Screw Terms	6350011023879
SC648M	68 – 80 dBa	2900 Hz	10-48 Vdc	5 – 20 mA	1.69 x 0.81”	Screw Terms	6350011406693
SC648MA	68 – 80 dBa	2900 Hz	10-48 Vac/dc	4 – 19 mA	1.69 x 1.38”	Screw Terms	
SC648MAH	68 – 80 dBa	4500 Hz	10-48 Vac/dc	4 – 18 mA	1.69 x 1.38”	Screw Terms	
SC648MD	60 – 75 dBa	1900 Hz	10-48 Vdc	5 – 20 mA	1.69 x 0.81”	Screw Terms	6350014609316
Loud Sound Level- Fast Pulse Tone (2 - 10 pps)							
SC628MNP	80 – 90 dBa	2900 Hz	6-28 Vdc	4 – 16 mA	1.69 x 1.38”	Screw Terms	6350013261784
Medium Sound Level- Fast Pulse Tone (2 - 10 pps)							
SC628MP	68 – 80 dBa	2900 Hz	6-28 Vdc	4 – 16 mA	1.69 x 1.38”	Screw Terms	6350000033534
							6350004128037
							6350014631106
SC628MHP	68 – 80 dBa	4500 Hz	6-28 Vdc	4 – 16 mA	1.69 x 1.38”	Screw Terms	6350011740085
Medium Sound Level- Fast Warble Tone (Requires use of SC628MD or SC628MH)							
SC628MW	68 – 80 dBa	2900 Hz	6-28 Vdc	4 – 16 mA	1.69 x 1.38”	Screw Terms	6350011983843
Medium Sound Level- Dual Tone: Continuous or Fast Pulse Tone (2 -10 pps)							
SC616MPU	68 – 78 dBa	2900 Hz	6-16 Vdc	3 – 12 mA	1.69 x 0.81”	Screw Terms	6350014136533

Call 317-612-1000 or Visit www.mallory-sonalert.com for More Details