





MALLORY SONALERT PRODUCTS, INC.

Product APPLICATION Guide



Tamper-Proof Panel Mount

Tamper-Proof Panel Mount- Continuous Tone

RoHS Part No.	Sound Level @ 12Vdc @ 1 ft (30 cm)	Freq. (Hz)	Operating Voltage	Current @ 12 Vdc (mA)	Size Dia x Len (mm)	Termination Type
PK-27A35ERQ	95	3500	3-24 Vdc	15	37 x 24	Screw Terms
PK-27A35EPQ	95	3500	3-24 Vdc	15	37 x 24	Flat Blades
PK-27N35ERQ	90	3500	3-28 Vdc	15	37 x 24	Screw Terms
PK-27N35EPQ	90	3500	3-28 Vdc	15	37 x 24	Flat Blades

Tamper-Proof Panel Mount- Fast & Slow Pulse Tone

Past Pulse Tone (3 pps)						
PF-27A35ERQ	95	3500	3-24 Vdc	15	37 x 24	Screw Terms
PF-27A35EPQ	95	3500	3-24 Vdc	15	37 x 24	Flat Blades
PF-27N35ERQ	90	3500	3-28 Vdc	15	37 x 24	Screw Terms
PF-27N35EPQ	90	3500	3-28 Vdc	15	37 x 24	Flat Blades
Slow Pulse Tone (1.2 pps)						
PL-27A35ERQ	95	3500	3-24 Vdc	15	37 x 24	Screw Terms
PL-27A35EPQ	95	3500	3-24 Vdc	15	37 x 24	Flat Blades
PL-27N35ERQ	90	3500	3-28 Vdc	15	37 x 24	Screw Terms
PL-27N35EPQ	90	3500	3-28 Vdc	15	37 x 24	Flat Blades

Tamper-Proof Panel Mount- Dual Tone

Continuous or Fast Pulse (3 pps)						
PFD-27A35ERQ	95	3500	3-24 Vdc	15	37 x 24	Screw Terms
PFD-27A35EPQ	95	3500	3-24 Vdc	15	37 x 24	Flat Blades
PFD-27N35ERQ	90	3500	3-28 Vdc	15	37 x 24	Screw Terms
PFD-27N35EPQ	90	3500	3-28 Vdc	15	37 x 24	Flat Blades
Continuous or Slow Pulse (1.2 pps)						
PLD-27A35ERQ	95	3500	3-24 Vdc	15	37 x 24	Screw Terms
PLD-27A35EPQ	95	3500	3-24 Vdc	15	37 x 24	Flat Blades
PLD-27N35ERQ	90	3500	3-28 Vdc	15	37 x 24	Screw Terms
PLD-27N35EPQ	90	3500	3-28 Vdc	15	37 x 24	Flat Blades

Call 317-612-1000 or Visit www.mallory-sonalert.com for More Details